# **THE MOST EFFICIENT** EPA-Certified Stick Wood Burning Appliances<sup>\*</sup>

### Keep your house as warm as you want and eliminate your oil, gas or electric heat bill.



TITANIUM HDX Outdoor Wood Furnaces



The Classic Edge HDX outdoor wood furnace is easy to operate and maintain. Models to match many installation scenarios are available.

- Value AND performance the revolutionary new patent-pending design of the Classic Edge Titanium HDX combines value and performance without sacrificing Central Boiler quality, reliability and performance.
- **Up to 60% less wood** compared to traditional and some other methods of wood heating.
- Stainless steel firebox constructed of titaniumenhanced stainless steel, the inside of the firebox is impervious to corrosion and provides excellent heat transfer performance.


- Easy to maintain firebox design and heat exchanger system make for easy maintenance and cleaning.
- **Easy to operate** FireStar combustion controller takes the guesswork out of operating.
- Monitor your furnace anywhere FireStar



combustion controller with onboard Wi-Fi keeps you in constant contact with your Central Boiler furnace if you're away. FireStar can even send you reminders such as when to add wood.

6-Month Same-As-Cash<sup>1</sup> or **8.99%** for up to 12 Years<sup>2</sup>

See back page for financing details and other important information.





CLASSIC EDGE 360 TITANIUM HDX

Overall Efficiency (LHV) - 88.4%\* Overall Efficiency (HHV) - 82.2%\* Mfr's Rated Heat Output Capacity -150,000 Btu/hr Heat Output (12 hr) - 66,894 Btu/hr

EPA Certified for residential use Firebox Volume - 10 cubic ft Firebox Dimensions - 28"L x 29"H x 21"W Door - 16"W x 16"H Ash Cleanout Door - 18"W x 9"H Water Capacity - 150 gal. Weight - 1,365 lbs One set of 1-1/4" Supply and Return Ports\*\* \*\*Can be configured for two pumps.

Furnace Options and Accessories: • LED Light Kits • Pump Panel Extension Kit



CLASSIC EDGE 560 TITANIUM HDX

Overall Efficiency (LHV) - 90.2%\* Overall Efficiency (HHV) - 83.8%\* Mfr's Rated Heat Output Capacity -200.000 Btu/br

Heat Output (12 hr) - 92,417 Btu/hr

EPA Certified for residential use Firebox Volume - 14 cubic ft Firebox Dimensions - 33"L x 32"H x 23"W Door - 18"W x 18"H Ash Cleanout Door - 18"W x 9"H Water Capacity - 205 gal. Weight - 1,668 lbs One set of 1-1/4" Supply and Return Ports\*\* \*\*Can be configured for two pumps. Bypass Door and Alarm

Furnace Options and Accessories: • LED Light Kits • Pump Panel Extension Kit



CLASSIC EDGE 760 TITANIUM HDX

Overall Efficiency (LHV) - 89.8%\* Overall Efficiency (HHV) - 83.4%\* Mfr's Rated Heat Output Capacity -245,000 Btu/hr

Heat Output (12 hr) - 146,686 Btu/hr

EPA Certified for residential use Firebox Volume - 23 cubic ft Firebox Dimensions - 37"L x 44"H x 26"W Door - 21"W x 25"H Ash Cleanout Door - 19"W x 11"H Water Capacity - 330 gal. Weight - 2,036 lbs One set of 1-1/4" Supply and Return Ports Two sets of 3/4" Supply and Return Ports Bypass Door and Alarm

Furnace Options and Accessories: • LED Light Kits



CLASSIC EDGE 960 TITANIUM HDX

Overall Efficiency (LHV) - 92.1%\* Overall Efficiency (HHV) - 85.6%\* Mfr's Rated Heat Output Capacity 400,000 Btu/hr

Heat Output (12 hr) - 212,957 Btu/hr

EPA Certified for residential use Firebox Volume - 32 cubic ft Firebox Dimensions - 42.75"L x 43.5"H x 31.5"W Door - 22.75"W x 28.75"H Ash Cleanout Door - 20"W x 11"H Water Capacity - 420 gal. Weight - 2,714 lbs One set of 1-1/4" Supply and Return Ports Two sets of 3/4" Supply and Return Ports Bypass Door and Alarm

Furnace Options and Accessories: • LED Light Kits

# CLASSIC TITANIUM

"We set our thermostat at 75° F and have not bought any fuel oil since we installed our Central Boiler furnace four years ago."

As the outdoor wood furnace that set the standard for quality and revolutionized the industry, the Classic is the perfect choice for heating your business, shop, barn and more. Check with your local Central Boiler dealer today. *In the U.S., the Classic is for non-residential applications only.* 



Heat Transfer Area - 52 sq ft Door - 20"W x 20"H Firebox - 40"L x 30"H x 26"W Water Capacity - 140 gal. Weight - 1,140 lbs Heat Transfer Area - 74 sq ft Door - 23"W x 23"H Firebox - 50"L x 36"H x 30"W Water Capacity - 196 gal. Weight - 1,492 lbs Heat Transfer Area - 119 sq ft Door - 23"W x 31"H Firebox - 60"L x 48"H x 36"W Water Capacity - 393 gal.

Weight - 2,140 lbs

Heat Transfer Area - 179 sq ft Door - 30"W x 40"H Firebox - 72"L x 60"H x 40"W Water Capacity - 764 gal. Weight - 3,336 lbs



Freedom to do more - With a Maxim outdoor wood pellet furnace, you'll have more time because of the large integrated hopper and extended burn times.



The Maxim M255 PE is U.S. EPA Step 2 Certified.

#### Maxim M255 PE

Door - 15.5"W x 13.5"H Water Capacity - 90 gal. Weight - 1,310 lbs Hopper Capacity - 11 Bushel (600 lbs) FireStar Combustion Controller

<sup>1</sup>6 Months Same-As-Cash - Credit and loans provided by Regions Bank d/b/a EnerBank USA, Member FDIC, (650 S Main St, Suite 1000, Salt Lake City, UT 84101) on approved credit, for a limited time. 19.99% fixed APR, effective as of September 2023, subject to change. Minimum loan amounts apply. Interest starts accruing when funds are disbursed. Interest is waived if repaid in 180 days from first disbursement. When open line period ends, the balance becomes a fixed rate installment loan; repayment terms vary from 18 to 126 months. Actual loan term may be shorter if less than the full approved amount of credit is used. First monthly loan payment due 180 days after first disbursement. <sup>2</sup>As Low as 8.99% Traditional Installment Loan - Credit and loans provided by Regions Bank d/b/a EnerBank USA, Member FDIC, (650 S Main St, Suite 1000, Salt Lake City, UT 84101) on approved credit, for a limited time. 8.99% fixed APR, subject to change. Minimum loan amounts apply. Interest starts accruing when funds are disbursed. Open line period amount of credit is used. First monthly thereafter during open line period ends, the balance becomes a fixed rate installment loan; repayment terms vary from 12 to 144 months. Actual loan term may be shorter if less than the full approved amount of credit is used. First monthly loan payment due 30 days from the end of the open line period. Minimum monthly payments vary between \$11.37 and \$94.80 per \$1,000 borrowed. The minimum monthly payment will be no less than \$50.00.



## CentralBoiler.com